

20m CONSTANT CURRENT LED STRIP SERIES

2835-140-10mm-20m

48V




IP rate


IP20 IP65 IP66 IP67 IP68

DC 48V CE 1 BIN Dimmable LM 80 Ra 80/90/95 120° 5 years

Illuminance Distribution



Dimensions & available lengths



Aluminum Profiles



Electrical & Output Data

Model No.	SW-F2835X70-WF0-20M-C-48-K010
Step length (mm/x LED)	100mm/14LEDs
Number LED/m	140
Voltage (v)	48 V
Ra	80 /90 / 95
Beam Angle(°)	120
Power (w/m)	12.8
FPC width (mm)	10
Max. length per circuit (m)	20
IP rate	20/67
Installation	3M Tape / Mounting Clips / Aluminum Profiles

The electrical data provided on the each product pages are for reference only; the data values are not guaranteed. Specification may be subject to change without announcement.

Light efficiency & Lumen Output

Luminaire efficacy (3000K)	108lm/W @Ra80	89.6lm/W @Ra90
LED color	Ra80	Ra90
	◇ = Popular Color	× = Niche Color
2300K	× 1217lm	× 1010lm
2500K	× 1272lm	× 1044lm
2700K	◇ 1327lm	◇ 1090lm
3000K	◇ 1382lm	◇ 1147lm
3500K	× 1410lm	× 1170lm
4000K	◇ 1486lm	◇ 1232lm
5000K	× 1438lm	× 1228lm
6000K	◇ 1438lm	◇ 1228lm